



L25-ek

SPECIFICATION

*Cod.AA00125 - Pass-through dishwasher Volt 400/3/N 50Hz

- *Straight or corner version
- *Stainless steel construction 18/10 AISI 304
- *Hood and tank with double insulating wall
- *Rotating lower and upper wash arms in stainless steel
- *Rotating lower and upper rinse arms in stainless steel
- ***Soft-touch electronic control panel**
- ***New control panel with interactive graphic display**
- ***Digital thermometers**
- ***Complete programming of all the washing parameters**
- ***Cycle counter**
- ***Service maintenance function**
- ***Constante rinse boiler system (RCB)**
- ***Rinse-aid dispenser**
- *Tank Self washing wash cycle
- *Economy thermostat
- *Thermocontrol
- *Drawn tank with self-cleaning bottom
- *Integral tank drawer filters
- *Automatic cycle start at hood shutting
- *Automatic tank loading
- *Safety device for hood opening
- *Certifications : CE

*Accessories :

- 2 baskets in plastic for 12÷18 dishes
- 1 general basket
- 1 basket in white rilsan steel for 24 dishes
- 2 cutlery containers



OPTIONAL

- cod.AC00035 – Rinsing Incorporated booster pump
- cod.AC00125 - Entry or exit side table with lower shelf 700mm
- cod.AC00550 – Drain unit with filter

| | | |
|-------------------------------|-----------------------------|---------|
| *DIMENSIONS : | 670 x 765 x 1475h | mm |
| *CAPACITY PER HOUR dishes | 1080/540/360 (1440) | Nr. |
| *CYCLE PERIOD | 60"/120"/180"/endless cycle | seconds |
| *BASKET DIMENSIONS | 50 x 50 | cm |
| *DISHES PER BASKET | 12-18 (24) | Nr. |
| *DISH CLEARANCE | 415 | mm |
| *STAINLESS STEEL WASHING PUMP | 1100 | W |
| *TANK ELEMENT | 6000 | W |
| * BOILER ELEMENT | 9000 | W |
| *TOTAL POWER | 10.100 | W |
| * TANK CAPACITY | 34 | Liters |
| * BOILER CAPACITY | 8 | Liters |
| *WATER CONNECTIONS | 45÷50 | °C |